

- **BLI-28000 (Monitor & Sensor)**

- Weight: 1.7 lbs (.75kg)
- Box Dimensions
  - Width: 8.3 in (21.1 cm)
  - Height: 8.5 in (21.6 cm)
  - Depth: 4 in (10.2 cm)
- Power Requirements
  - Sensor: Standard - 2 alkaline AA 1.5 volt (LR6 type)
  - Extreme cold weather - 2 lithium AA 1.5 volt (L91 type)
  - Display: Standard 2 alkaline AA 1.5 volt (LR6 type)
- Communication Range
  - Frequency: 433 MHz
  - Range: approximately 30m (100 ft) - subtract 5m (15ft) for each wall between sensor and monitor
- Updates from Sensor to Display Unit: every 30 seconds
- Operating Temperature
  - Display Unit: 10°C to 45°C (50°F to 113°F)
  - Sensor Unit: -40°C to 60°C (-40°F to 140°F)
- Warranty
  - 1 year material defects or workmanship. Replacement or refund at manufacturer's discretion
- Accuracy
  - $\pm 1\%$  at meter
- Meter Types
  - Compatible with most traditional electromechanical disc meters, digital meters, AMR, AMI and Smart Meter technologies.
  - kH factor setting 0.1 - 99.9